

موتور برق



دیزل نیرو

واردات و فروش انواع موتور برق های خانگی و صنعتی



Product Description

- * Easier and more convenient electric starter
- * New AVR(Automatic Voltage Regulator) stabilizes the output power
- * Low oil level alarming system will automatically stop the generator when lube oil is less than the set value
- * A traditional open frame generator with a rugged and durable frame

[OPERATIONAL MANUAL](#)
[SPEC SHEET](#)

Features

Specs

Model	KDE6500E
Rated frequency (Hz)	50 60
Rated output (kVA)	4.5 5.0
Max. output (kVA)	5.0 5.5
Rated Voltage (V)	115/230 120/240
Rated current (A)	39.1/19.6 41.7/20.8
Rated rotation speed (r/min)	3000 3600
Phase NO.	Single phase
Power factor (Cos Φ)	1.0
Insulation Grade	B
Pole number	2
Excitation mode	Self-excitation & constant voltage (AVR)
Panel Type	General Panel
Voltage (V)	115/230 120/240
Receptacle	Two receptacles
Connection pole	Without
DC12V output	Connection pole output
Overall dimension (L×W×H) (mm)	720X492X655
Dry weight(kg)	100
Working assorting weight (Kg)	115
Noise level (7m) dB(A)	77
Structure type	Open frame
Engine Model	KM186FAG
Engine Type	Single cylinder, vertical, four-stroke, direct injection, air-cooled
Cylinder NO.-bore×stroke (mm)	1-86×72
Displacement (ml)	418
Rated power [KW/(r/min)]	5.7/3000 6.3/3600
Compression ratio	19:1
Lubrication system	Pressure splashed
Starting system	Recoil starter
Fuel type	0 # (summer) -10 # (winter) -35 # (chillness) diesel
Lube oil brand	CD grade or SAE10W-30, 15W-40
Capacity of cooling water (L)	Without
Lube capacity (L)	1.65
Starting motor capacity (V-kW)	12V 0.8kW
Charging generator capacity (V-A)	12V 3A
Battery capacity (V-Ah)	12V 36Ah
Fuel consumption (g/kW.h)	≤360
Fuel tank capacity (L)	13.5
Continuous running time (hr)	5.5