

موتور برق



دیزل نیرو

واردات و فروش انواع موتور برق های خانگی و صنعتی



Rate frequency(Hz)	50 60
Rated voltage(V)	230 230
Rated current(A)	7.4 7.8
Rated output power(kW)	1.7 1.8
Rated rotation speed(rpm)	3000 3600
Welding voltage at zero load(V)	65
Rated welding DC current(A)	180
Rated voltage(V)	25~30
Welding load continuous ratio	50%
Current rectorgulation range(A)	80~200
Power factor(cos)	1.0
Phase number	Single phase
Noise level[dB(A)@7m]	70~74
Overall dimension(L*W*H)[mm(in)]	910x530x710(35.83x20.87x27.95)
Dry weight[kg(ibs.)]	177(389.40)
Structure type	Silent type
Continuous running time(at rated load)	12hours
Excitation mode	Self-excitation and constant voltage(AVR)
Starting system	12V electric starter
Engine model	KM186FAE
Engine type	Single cylinder, 4-stroke, air-cooled, direct diesel engine
Displacement[ml(cu.in)]	418(25.51)
Compression ratio	19;1
Rated power[kW(HP)/rpm]	5.9(8.02)/3000,6.5(8.84)/3600
Fuel	0#or-10#light diesel oil
Lube	SAE10W30(above CC grade)
Fuel tank Capacity[L(gal.)]	15(3.3)
Lube Capacity[L(gal.)]	1.65(0.36)
Low oil pssure alert system	With

Specifications: